Installation Instructions

Audi side assist

Facelift

v1.8 (05.08.2019)

Contents

1 Liability Exclusion 3

2 Copyright 4

3 General notes 4

4 Safety Instructions 5

5 Requirements for the intended use 5

6 How to connect a cable to another 6

7 Note Cable Inscription/Color 7

8 Assembly instructions 8

9 Safety Instructions for working on Airbags 9

10 Note 9

11 Removing rear lights 10

12 Removing rear bumper 12

13 Installation sensors - until 2016 13

14 Installation sensors - from 2017 14

15 Hints for the further installation 15

16 Cable routing into the trunk - until 2016 16

17 Removing rear sill trim passenger's side 17

18 Removing front sill trim passenger's side 18

19 Cable routing to the door interconnecting point passenger's side 19

20 Connection door interconnecting point passenger's side 20

21 Removing trim panel dashboard 21

22 Removing trim panel driver's side 22

23 Cable routing to the driver's side 23

24 Connection CAN High & Low / ignition lead 24

25 Connection door interconnecting point driver's side 25

26 Removing door covering driver's side 26

27 Removing mirror driver's side 27

28 Alteration mirror 28

29 Connection additional wire door interconnecting point 30

30 Terminal coding - until 2016 31

31 Terminal coding - from 2017 **32**

32 Important Note Side Assist **32**

33 Bus rest **33**

8 Assembly instructions

The following illustration shows the cable routing as well as the position of the individual components.




Figure 3: Vehicle overview

- 1 Sensors (right sensor: master 566 - left sensor: slave 590)
- 2 Connection cable set
- 3 Warning lights

Please be aware, that this overview is only for **illustration purposes**. Always lay the cable set in the **most convenient and shortest way** possible. For a detailed description of the cable routing, please refer to the relevant sections of the following manual.