



Installation Instructions

Complete Set sensor-controlled tailgate opening
v1.0 (25.03.2019)

Contents

1	Liability Exclusion	3
2	Copyright	4
3	General notes	4
4	Safety Instructions	5
5	Requirements for the intended use	5
6	How to connect a cable to another	6
7	Note Cable Inscription/Color	7
8	Safety Instructions for working on Airbags	8
9	Assembly Instruction	9
10	Assembly Note	10
11	Disassembly covering driver's side	11
12	Disassembly trunk covering	13
13	Removing rear bumper	15
14	Cable routing	17
15	Connection cable set / Ground	18
16	Installation sensor in rear bumper	19
17	Coding with Coding Interface	20
18	Coding dongle	20
19	Assembling the vehicle	20
20	Bus rest	21
21	Activation function sensor-controlled tailgate opening	21
22	Connection / Troubleshooting cable set	22

8 Safety Instructions for working on Airbags

Working on Airbag systems has to be executed exclusively by especially trained qualified personnel.

Notes for working on Airbag systems:

- Remove the ignition key and disconnect the battery.
- Wait at least 5 minutes. Only then you can work on the Airbag systems.
- Discharge yourself before you work on an Airbag unit by touching the latch of the door.
- Airbag units which have been removed are always put down face up.
- During the works on the Airbag system you have to be very careful.
- Additionally, the safety notes of the corresponding manufacturer are valid.

Kufatec GmbH & Co. KG does not assume liability in any case of damage!